

# KENWOOD

## NEXEDGE®

# NX-240V/340U

NEXEDGE® VHF/UHF Digital & FM Portable Radios

## NXDN® FleetSync®

Your business will have to adopt digital radios sooner or later, you know that, but you probably wonder when to make the extra investment. A leap into the unknown? Not with the new NEXEDGE® NX-240V/340U. It operates in both analog FM and NXDN® digital modes, offering a cost-effective way to migrate smoothly from legacy systems while discovering the benefits of advanced digital technology – including increased effective coverage area, low noise for superior clarity, and inherent secured voice. All this comes in a tough, compact radio that is easy to operate, delivers high-powered audio, and ensures round-the-clock reliability. Don't delay the opportunity to expand the potential of your business.

### NXDN® DIGITAL AIR INTERFACE

NEXEDGE® radios employ NXDN®, an FDMA digital air interface with AMBE+2™ voice coding technology, unique filtering and a 4-level FSK modulation technique with low bit error rate (BER) even at weak RF signal strengths.

### ENHANCED AUDIO QUALITY

AMBE+2™ VOCODER technology accurately replicates natural human speech nuances for superior voice quality, even at highway speeds. Additionally, the powerful 36mm-diameter speaker delivers up to 1 watt audio output, providing undeniably clearer and crisper audio.

### ULTIMATE PERFORMANCE

RF output power is 5W for both VHF (NX-240V) and UHF (NX-340U). Additionally, the UHF frequency coverage on the NX-340U is 70MHz.

### ERGONOMIC DESIGN

The slim contours and ergonomic design of the NX-240V/340U make it comfortable to hold, while the dimples on both sides ensure a firm grip.

### 32 CHANNELS / 2 ZONES

The NX-240V/340U can be used with two conventional zones, offering up to 16 channels per zone.

### SWITCHABLE DIGITAL AND ANALOG DUAL MODES

The NX-240V/340U is effectively two radios in one – analog and digital – operating on 12.5kHz in analog zones, and on 6.25kHz NXDN® in digital zones. For convenience, a PF key can be used to switch between zones.

### 6.25kHz NXDN® DIGITAL CHANNEL

Digital communications are more spectrum-efficient and offer wider area coverage than analog.

### NXDN® CONVENTIONAL

Compatible with NEXEDGE® Digital Conventional Mode, this radio offers 64 RAN (Radio Access Numbers) and individual & conference group calling to ensure expeditious communications.

### HIGH SECURITY

Confidentiality in radio communications is a Kenwood priority, and helping to maintain a high level of security in analog mode is a 16-code voice inversion scrambler, while robust NXDN® encryption is available in digital mode.

### GPS CONNECTIVITY

The optional KMC-48GPS Speaker Microphone will enable GPS tracking applications to work with the NX-240V/340U. GPS data can be transmitted at programmed timing, or upon receiving a request.

### OTHER FEATURES

**DIGITAL:** • Over-The-Air Alias (TX only) • Paging Call  
• Individual Call & Conference Group Call • Status Messaging  
• Remote Monitor\* • Site Roaming\* • Late Entry • NXDN® ESN  
**ANALOG:** • FleetSync®, MDC-1200, DTMF • QT/DQT/2-tone  
• Compander • Squelch Level  
**GENERAL:** • Multiple Scan • 4-Color LED (Blue / Red / Green / Orange) • 2 PF Keys • 16-Position Mechanical Selector  
• Zone / Channel Number Voice Announcement • VOX Ready  
• Emergency Call • Remote Stun/Kill • Lone Worker Alert (per channel) • Time Out Timer • Busy Channel Lockout  
• Low Battery Warning • Battery Saver • KPG-170D Windows®  
FPU • Wireless Cloning • Password Protection • PTT Release  
Tone • Minimum Volume • Mic Sense • MIL-STD-810 C/D/E/F/G  
• IP54/55 Water & Dust Intrusion

\*Available in the future



## Options

■ **KNB-45L**  
2,000mAh/7.4V  
Li-Ion Battery Pack



■ **KRA-26**  
VHF Helical Antenna



■ **KMC-45**  
Speaker Microphone



■ **KHS-31**  
C-Ring PTT Ear  
Hanger Headset



■ **KSC-35SK**  
Rapid Charger  
For the KNB-45L  
(3-Hour)



■ **KRA-27**  
UHF Whip Antenna



■ **KHS-26**  
Earbud In-line  
PTT Headset



■ **KMB-28**  
Six Unit Charger  
Adapter (for six  
KSC-35SK chargers)



■ **KVC-22**  
DC Vehicular  
Charger Adapter



■ **KMC-48GPS**  
GPS Speaker Microphone



■ **KHS-27**  
D-Ring In-line  
PTT Headset



■ **KBH-10**  
Belt Clip



■ **KLH-187**  
Nylon Case



All accessories and options may not be available in all markets.  
Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

## Main Specifications

		NX-240V	NX-340U
GENERAL			
Frequency Range		136-174 MHz	450-520 MHz
Number of Channels		32	
Zones		2	
Max. Channels per Zone		16	
Channel Spacing	Analog	12.5 kHz	
	Digital	6.25 kHz	
Operating Voltage		7.5V DC ± 20%	
Battery Life		Approx. 10/12 hours	
5-5-90 during hi-power battery saver: OFF/ON with KNB-45L (2000mAh)			
Operating Temperature Range		-22°F ~ +140°F (-30°C ~ +60°C)	
Frequency Stability		±2.0ppm	±1.0ppm
Antenna Impedance		50 Ω	
Dimensions (W x H x D)	With KNB-45L, Projections Not Included	2.13 x 4.8 x 1.39 in (54 x 122 x 35.3 mm)	
Weight (net)	Radio only	5.8 oz (165 g)	
	With KNB-45L	9.9 oz (281 g)	
FCC ID		ALH443700	ALH443800

		NX-240V	NX-340U
RECEIVER			
Sensitivity	Digital		0.25 μV
	Analog (12 dB SINAD)		0.25 μV
Selectivity	Analog		60 dB
Intermodulation Distortion	Analog		60 dB
Spurious Response	Analog		70 dB
Audio Distortion			Less than 10%
Audio Output		1 W / 12 Ω (Internal Speaker) 500mW / 8 Ω (External Output)	
TRANSMITTER			
RF Power Output	High / Low	5 W / 1 W	
Spurious Response			70 dB
FM Hum & Noise	Analog		40 dB
Audio Distortion			Less than 10%
Modulation		11K0F3E, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D	

Specifications are subject to change without notice, due to advancements in technology.  
Measurements made per TIA/EIA-603 and Specification are typical.

FleetSync® is a registered trademark of JVCKENWOOD Corporation.

Windows® is a registered trademark of Microsoft Corporation in the United States and other countries.

AMBE+2™ is a trademark of Digital Voice Systems Inc.

NXDN® is a registered trademark of JVCKENWOOD Corporation and Icom Inc.

NEXEDGE® is a registered trademark of JVCKENWOOD Corporation.

## Applicable MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV	516.6/Procedure I, IV
International Protection Standard					
Dust & Water Protection	IP54/55*				

\*To meet MIL-810 and IP grade, the 2-pin connector has to be connected.

## ACCESSORIES INCLUDED

- KNB-45L Li-ion Battery Pack
- KSC-35S Rapid Charger
- KRA-26/27 VHF Helical Antenna/UHF Whip Antenna
- KBH-10 Belt Clip
- Channel Stopper

**Kenwood U.S.A. Corporation**  
Communications Sector Headquarters  
3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265

**Order Administration/Distribution**  
P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

**Kenwood Electronics Canada Inc.**  
Canadian Headquarters and Distribution  
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8  
www.kenwood.ca



CL775KM-E-2