

EC1MV3-MT19T

Motorola APX Series Single-Unit In-Vehicle Charger

FOR MOTOROLA APX6000 / APX6000XE / APX7000 /
APX7000XE / APX8000 / APX8000XE



Features the exclusive "MT19T" charging pod and firmware, enabling proper charging of 8.4V and 8.7V APX batteries.



SPECIFICATIONS – EC1MV3-MT19T

DIMENSIONS (W X L X H)	96 x 131 x 77 mm / 3.8 x 5.2 x 3.0 in
WEIGHT	0.25 kg / 0.55 lbs. (charger only)
COMPATIBLE CHEMISTRIES	Li-Ion / LiPo / NiMH
CHARGER INPUT	12V-24V DC / 1.0A (minimum)
CHARGE RATE	900 mA (10.6V-13.5V)
APPROVALS	FCC ^A / BC ^B / DOE ^C / CE

Specifications subject to change without notice.

(A) Complies with FCC Rules, Part 15, Subpart B, Class B 2016, ANSI C63.4:2014. (B) Complies with California Energy Commission CEC-400-2011-005. (C) Complies with U.S. Department of Energy 10 CFR, Part 430, PC3 and 4. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.



PM4486LIPIC
Replaces PN: PMNN4486
3400 mAh / IP68 Rated
2-year Warranty



LEVCA-MT19
APX6000, APX6000XE, APX7000,
APX7000XE, APX8000, APX8000XE



PM4487LIPIC
Replaces PN: PMNN4487
4900 mAh
2-year Warranty



EC6MV3-MT19
APX6000, APX6000XE, APX7000,
APX7000XE, APX8000, APX8000XE

- EC1MV3-MT19T properly charges batteries with higher voltage requirements, including PMNN4485, PMNN4486, PMNN4504, and PMNN4494.
- EC1MV3-MT19T provides hot and cold battery monitoring to ensure safe charging and prevent battery damage.
- EC1MV3-MT19T includes vehicle power adapter and bracket for floor or dash mounting.