

Kenwood NX5000 Series EC12M-KW4A-D*

FOR KENWOOD NX5200 / NX5300 / NX5400 / TK5230 /
TK5330 / TK5430 / VP5000 Series / VP6000 Series



SPECIFICATIONS – EC12M-KW4A-D

DIMENSIONS (W X L X H)	509 x 148 x 94 mm / 20.0 x 5.8 x 3.7 inches
WEIGHT	1.63 kg / 3.6 lbs (charger only)
COMPATIBLE CHEMISTRIES	Li-Ion / LiPo / NiMH / NiCd
CHARGER INPUT	12-24V DC / 10.0A (minimum)
CHARGE RATE	800 mA (10.6V – 13.5V)
APPROVALS	FCC ^A / BC ^B / DOE ^C / CE

Specifications subject to change without notice.

(A) Complies with FCC Rules, Part 15, Subpart B, Class B 2016, ANSI C63.4:2014. (B) Complies with California Energy Commission CEC-400-2011-005. (C) Complies with U.S. Department of Energy 10 CFR, Part 430, PC3 and 4.



Intrinsically Safe

LEKNBL2LIIS

3400 mAh / Li-Ion

Same capacity as KNB-L3M,
but thinner

1-year Warranty



BPKNBL2LI-34

3400 mAh / Li-Ion

Same capacity as KNB-L3M,
but thinner

1-year Warranty



BPKNBL2LI-26

2600 mAh / Li-Ion

Replaces KNB-L1M and
KNB-L2M

1-year Warranty



ESM-28-KW2

Speaker Mic

IP67 Rated

Extra Loud Audio

3-year Warranty



EC1M-KW4A

Single Unit Charger
with Replaceable
Charging Pod
2-year Warranty

*Also Charges: NX200S, NX210, NX210G, NX300, NX300S, NX410, NX411, NX5300, NX5400, TK3180, TK5210, TK5210G, TK5220, TK5230, TK5310, TK5310G, TK5320, TK5330, TK5410, TK5430, VP5230, VP5330, VP5430, VP6230, VP6330, VP6430.
Compatible with KNB-41NC / KNB-73LCM (IS batteries). Not compatible with KNB-50NC / KNB-72LC / KNB-L5S (IS batteries).

EC12M-KW4A-D FEATURES

- Properly charges Kenwood KNB-L1M/L2M/L3M batteries.
- Provides cold and hot battery monitoring for batteries with temperature sensing circuitry.
- Includes AC to DC power supply and six dual position charging pods. Single, dual and 6-unit models also available.
- Additional accessories available for in-vehicle use.